

Uno 200™



Adapted to Your Everyday Needs

Uno 200 is a newly developed mobile lift from Liko, adapted to most frequent lifting situations, for instance in nursing homes and home care.

Uno 200 has the basic features, giving you a simple and reliable mobile lift without compromising safety or user-friendliness.

The wheels roll easily on most surfaces and adapt to the travel direction, which facilitates patient transfers.

Uno 200 also has electrical widening of the base and lifts up to 200 kg (440 lbs.). Uno 200 is unique in that the lift interval and the max. load can be adjusted by different settings, enabling you to adapt the mobile lift to your needs. Furthermore, with Liko's extensive accessory range, you can customize lifting solutions to fit the actual lifting situation and the patient.

And as usual with Liko, safety is in focus: Uno 200 has both mechanical and electrical emergency lowering and uses well proven technology, which is a security for both caregiver and patient.

Simple and Versatile

Uno 200 can be used in most commonly occurring lifting situations, for instance transfers between bed and wheelchair, to and from the toilet, and lifts to and from the floor.

With its three height adjustment possibilities, Uno can easily be adapted to provide optimal lifting height.

Uno's smart FlexLink (an extra link arm increasing the distance to the lift mast) provides for almost vertical lifting and greater flexibility when lifting from the floor.

If you equip Uno with a Quick-Release Hook, you can easily and without tools switch to another slingbar in Liko's extensive range.

A Quick Reference Guide can always be found in the lift pocket to remind caregivers of important operations.



Both the lift arm and the base-width adjustment on Uno 200 are operated easily and smoothly from the hand control - thus the caregiver can be close and create a secure lifting situation for the patient.

■ TECHNICAL DATA

Max. Load:	160/200 kg (350/440 lbs.) depending on settings
Lifting Speed:	22 mm/s (0.86"/s) without load, adjusted for max. load 160 kg (350 lbs.) 18 mm/s (0.70"/s) without load, adjusted for max. load 200 kg (440 lbs.)
Batteries:	2 12 V 2.9 Ah valve-regulated lead-acid gel batteries
Battery Charger:	100-240 VAC, 50-60 Hz, max 500 mA
Front Wheel:	75 mm (3") twin wheel
Rear Wheel:	75 mm (3") twin wheel with brakes
Emergency Lowering:	Mechanical and electrical
Protection Class:	IP X4
Material:	Painted steel with lacquer top coat.
Weight:	38.5 kg (85 lbs.)
Prod. No.:	2010020



Uno 200 has been tested by an accredited testing institute and complies with the requirements for Medical Device Directive Class I products (MDD 93/42/EEC).

Uno 200 complies with the requirements in IEC 60601-1, IEC 60601-1-2, SS-EN ISO 10535, UL-60601-1 and CAN/CSA C22.2 No. 601.1.

Design and Quality by Liko in Sweden.

Liko is quality certified in accordance with ISO 9001 and its equivalent for the medical device industry, ISO 13485.

Liko is also certified in accordance with environmental standard ISO 14001.



www.liko.com

Manufactured by:

Liko AB
Nedre vägen 100
975 92 Luleå
Sweden
info@liko.se

Local representative in UK

Hill-Rom Limited
Clinitron House, Ashby Park
Ashby de la Zouch,
Leicester LE65 1JG
Tel: 01530 411000
Fax: 01530 411555
info@liko.co.uk

To find your local Liko representative,

please visit www.liko.com or call
+46 (0)920 47 47 00



A Hill-Rom Company